

Product Specifications

FlashLink. USB Reusable Data Logger

Measurement Range	-40°F to 149°F (-40°C to 65°C)
Temperature Resolution	0.1°F/°C
Accuracy	±1.0°F from 14°F to 77°F (±0.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C)
Data Capacity	3823 points
Data Download Time	2 seconds typical for 3823 points
Programmable Alarm Levels	High & Low levels over entire range, displayed on LCD
Battery	(CR2032) 3.6V Lithium/18 months
Dimensions/Body	1.575" x 3.189" x .575" (40mm x 81mm x 13mm)
Casing	PC/ABS plastic
Weight	1.3 oz. (36 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, NIST traceable, RoHS Compliant
Display	LCD, Red LED Alarm
Waterproof Rating	IP67 with silicon cap on
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
System Requirements	Windows PC with current operating system Adobe Reader
Programming	FlashPDF Program Manager software or USB Program Manager software
Download Requirements	Direct USB connection



Model 20908

- Single channel, internal sensor for ambient air temperature
- User Programmable: manual or automatic start, sample interval, alarm limits, data tags
- Large, easy to read LCD display
- Trip history statistics available on LCD
- NIST traceable and CE Mark
- USB Connection

Patent No. 6,088,514



DeltaTrak manufactures products under an ISO 9000 registered quality management system

SS0077 16D1

